

03-27-00

EXPRESS MAILING NO. 97245390471US

412 Rec'd PCT/PTO 24 MAR 2000

PCT/8

FORM PTO-1390
(REV 11-98)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371

P-3002.1

U.S. APPLICATION NO. (If known, see 37 CFR 1.5)

09/509433

INTERNATIONAL APPLICATION NO
PCT/GB98/02905

INTERNATIONAL FILING DATE
25.09.98

PRIORITY DATE CLAIMED
25.09.97

TITLE OF INVENTION

OPTICAL IRRADIATION DEVICE

APPLICANT(S) FOR DO/EO/US

The University of Bristol Intellectual Property Management Unit

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☐ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☐ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern document(s) or information included:

11. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☐ A **FIRST** preliminary amendment.
☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☐ Other items or information:

U.S. APPLICATION NO. (if known, see 37 CFR 1.5) 09/509433		INTERNATIONAL APPLICATION NO. PCT/GB98/02905		ATTORNEY'S DOCKET NUMBER P-3002.1	
---	--	---	--	--------------------------------------	--

17. ☒ The following fees are submitted:
BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) :
 Neither international preliminary examination fee (37 CFR 1.482)
 nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO
 and International Search Report not prepared by the EPO or JPO \$970.00
 International preliminary examination fee (37 CFR 1.482) not paid to
 USPTO but International Search Report prepared by the EPO or JPO \$840.00
 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but
 international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$760.00
 International preliminary examination fee paid to USPTO (37 CFR 1.482)
 but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$670.00
 International preliminary examination fee paid to USPTO (37 CFR 1.482)
 and all claims satisfied provisions of PCT Article 33(1)-(4) \$96.00

ENTER APPROPRIATE BASIC FEE AMOUNT =		CALCULATIONS	PTO USE ONLY
		\$ 840.00	

Surcharge of \$130.00 for furnishing the oath or declaration later than ☐ 20 ☐ 30
 months from the earliest claimed priority date (37 CFR 1.492(e)).

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	CALCULATIONS	PTO USE ONLY
Total claims	30 - 20 =	10	X \$18.00	\$ 180.00	
Independent claims	5 - 3 =	2	X \$78.00	\$ 156.00	
MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ \$260.00		
TOTAL OF ABOVE CALCULATIONS =				\$ 1,176.00	

Reduction of 1/2 for filing by small entity, if applicable. A Small Entity Statement
 must also be filed (Note 37 CFR 1.9, 1.27, 1.28).

SUBTOTAL =				\$ 1,176.00	
-------------------	--	--	--	-------------	--

Processing fee of \$130.00 for furnishing the English translation later than ☐ 20 ☐ 30
 months from the earliest claimed priority date (37 CFR 1.492(f)).

TOTAL NATIONAL FEE =				\$ 1,176.00	
-----------------------------	--	--	--	-------------	--

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be
 accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property +

TOTAL FEES ENCLOSED =				\$ 1,176.00	
------------------------------	--	--	--	-------------	--

	Amount to be:	\$
	refunded	
	charged	\$


a. ☒ A check in the amount of \$ 1,176.00 to cover the above fees is enclosed

b. ☐ Please charge my Deposit Account No. _____ in the amount of \$ _____ to cover the above fees.
 A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any
 overpayment to Deposit Account No. 50-0852. A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:
 John C. Evans
 Reising, Ethington, Barnes, Kisselle,
 Learman & McCulloch, PC
 248-689-3500


 SIGNATURE:
 John C. Evans
 NAME
 20,124
 REGISTRATION NUMBER

TECHNICAL FIELD

[illegible]

It has already been proposed to use light-emitting diodes LEDs in a hand held device to produce a focused beam of light to cure dental materials. Blue light at a peak wavelength of about 470nm is used to harden dental polymers which contain camphoroquinone as the photoinitiator in a methacrylate polymerisation process. However, there is a problem in producing a sufficient level of irradiance even with a clustered array of LEDs, to cure the known dental polymers in the recommended time. At the lower levels of irradiance available generally below 300mW/sq.cm, longer curing times have to be allowed, which reduces the efficiency of the dental treatment delivered.

An object of the present invention is to provide an optical irradiation device that employs LEDs, and thereby has the benefits of compactness, portability, ruggedness and long

life, but which also produces improved levels of irradiance at and above 300mW/sq.cm.

According to a first aspect of the invention, LEDs are clustered in an irradiation device by forming shaped facets on adjacent LEDs which allow them to adjoin more closely than they would otherwise with conventional spherical outer surfaces as manufactured currently.

According to a second aspect, the invention consists in a tapered light guide for an optical irradiation device, which light guide is tapered from its input end to its output end and has an intermediate region of minimum diameter in which a bend is formed.

According to a third aspect, the invention consists in an optical irradiation device employing LEDs and incorporating a heat pipe to cool the LEDs.

According to a fourth aspect, the invention consists in a heat pipe comprising inner and outer walls that extend longitudinally from one end of the heat pipe to the other and define an annular space therebetween containing a material that serves to absorb heat by a phase change, the annular space being divided by internal walls into a plurality of fluid flow channels that extend longitudinally between said

ends, some of said channels being adapted to conduct the liquid/vapour phase of said material from the hot end of the heat pipe to the cold end, and other channels being adapted to return said liquid phase from the cold end of the pipe to the hot end.

According to a fifth aspect, the invention consists in an irradiation device employing LEDs and a tapered light guide to collect radiation emitted by the LEDs and deliver this to an output beam, wherein two or more tapered light guides are arranged in series so that successive guides receive radiation from preceding guides, and a group of LEDs is provided at the input end of each guide, each successive guide preferably being provided with a ring of LEDs around the output end of the preceding guide.

The first aspect of the invention means that LEDs occupy more of the available space, and a fixed number produce a higher radiant intensity. Thus, smaller numbers of LEDs can be used to produce a desired level of irradiance, which in turn reduces the power required to drive the device and the heat generated by it. Furthermore, the device can be made more compact. Packing of the LEDs in this way may involve a slight reduction in the output of each LED, but the more effective packing density produces an overall increase in irradiance.

Typically, a central LED might have a polygonal outer surface, and a first ring of LEDs would be arranged around it, each with a flat face to abut a corresponding face of the central LED and possibly each having a pair of radiating side faces which abut adjacent LEDs in the first ring. Furthermore, a second or more rings of LEDs could be arranged concentrically with the first ring, each with respective adjacent flat side faces abutting one another and possibly with inwardly diverted faces abutting respective outwardly directed faces of the LEDs of the inner ring. Alternatively, a single ring or two or more concentric rings of LEDs could be used without a central LED.

DESCRIPTION OF THE DRAWINGS

The invention will now be described by way of example with reference to the accompanying drawings, in which:

Figure 1 is a schematic cross-section through a first embodiment of the invention comprising a cluster of hexagonal section LEDs;

Figure 2 is a schematic cross-section through a second embodiment of the invention comprising a cluster of an inner group of LEDs and an outer ring of LEDs;

Figure 3 is a schematic cross-section through a third embodiment of the invention comprising a cluster of two rings of LEDS;

Figure 4 is a schematic side elevation of a fourth embodiment of the invention;

Figure 5 is a schematic longitudinal section through a fifth embodiment of the invention;

Figure 6 is a schematic longitudinal section through a sixth embodiment of the invention;

Figure 7 is a schematic cross-section through a bundle of light guide fibres with modified sections;

Figure 8 is a schematic side elevation of a tapered light-guide according to another embodiment of the invention;
and

Figure 9 is a schematic cross-section through a heat pipe according to the invention.

MODE OF CARRYING OUT THE INVENTION

In a typical optical irradiation device according to the invention, a plurality of LEDs are clustered together so as to

direct emitted radiation into a single beam. A cluster of LEDs 43 is shown in side view in Figure 4, and in plan view or cross-section in Figures 1 to 3. Each LED comprises a light-emitting semiconductor Pn junction (not shown) which is encapsulated in an outer plastics envelope, the profile of which is shown in the drawings. The sides of the LED envelope are shaped to allow the LEDs to be clustered together more closely at their bases, thereby increasing the ratio of occupied to unoccupied space in the cluster of LEDs. The tips of the LEDs are substantially spherical and transmit the radiation to form the beam.

In the embodiment of the invention illustrated in Figure 1 the outer envelope of the LEDs is hexagonal in cross-section, and the LEDs are clustered in the manner of a honeycomb as shown, with adjacent facets abutting one another.

In the second embodiment of the invention illustrated in Figure 2, a central LED 21 of hexagonal cross-section has facets which abut adjacent facets of six LEDs 22 in a first ring of LEDs with radially extending side facets that allow adjacent LEDs in the ring to abut one another. A second ring of LEDs 23 is arranged around the first ring of LEDs, and these LEDs 23 have radially extending side facets that allow adjacent LEDs in the ring to abut one another.

In a third embodiment of the invention shown in Figure 3, an inner ring of nine LEDs 31 in a first ring is contained within a second ring of LEDs 32, and radially extending side facets of the LEDs in both rings allow adjacent LEDs in each ring to abut one another.

Both the second embodiment of Figure 2 and the third embodiment of Figure 3 may be modified by the addition of one or more further concentric rings of LEDs. Also, the circumferential facets of the LEDs of each ring may be shaped to abut similarly shaped circumferential facets of the adjacent ring of LEDs.

In yet another embodiment, the central group of LEDs 21,22 of Figure 2 may be replaced by the same number of LEDs in a honeycomb cluster. Yet another embodiment may consist of the single ring of LEDs 31 shown in Figure 3. It will be appreciated in all three illustrated embodiments, the LEDs are mounted in a substantially flat plane.

In modifying the conventional optical sphere shape of the outer plastics envelope of a LED care has to be taken to preserve as much as possible of the focusing effect of the envelope to maximise the total irradiance. However, because the envelope of existing LEDs have a tapered shape to assist their removal from the mould during manufacture, the shaped

The shaped facets of the LEDs may be polished to enhance reflection and help reduce any loss of optical powers. Additionally, a reflective metallic film may be applied to the shaped facets to further enhance reflection.

The electrical connections of the LEDs, known as lead frames 44, are connected to respective positive and negative power terminals or bus bars 42. Preferably, these terminals are adapted to serve the dual function of heat sinks to help remove heat generated by the LEDs 43. Thus, the terminals are formed of a good thermal conductor such as copper, and are located in the optimum location relative to the LEDs and the

The typical optical irradiation device according to the invention also preferably incorporates a tapered light guide, shown as guide 41 in Figure 4, to collect light emitted by the LEDs and deliver this as an output beam. It is known to use light guides with adiabatic optical tapers in optical irradiation devices so that there is total internal reflection of the light as it is conducted from the light source to the output. However, an advantage of the invention is that the more compact cross-section of the LED cluster means that the diameter at the input end of the light guide can be smaller, and thus a smaller angle of adiabatic taper (i.e. the ratio of the diameter of the input end to the output end of the light guide) can be provided in the light guide with the consequent more efficient transmission of radiant energy and increased illuminance. This improvement is most marked compared with a conventional approach of simply increasing the numbers of LEDs in a cluster at ever increasing diameters with decreasing

beneficial effect on illuminance and increasing detrimental effect on compactness, heat generation and cost.

In another embodiment of the invention, illustrated in Figure 6, two or more adiabatic tapered light guides 41 are arranged in series, each with a corresponding cluster of LEDs 43, but with successive clusters forming a ring around the end of one light guide as it connects to the next. Alternatively, each successive ring of LEDs 43 may be replaced by just one or a fewer number of LEDs. This arrangement allows the overall diameter of the device to be kept relatively small as the LED clusters 43 are arranged in groups along the length of the device.

In the preferred embodiment of Figure 4, a single tapered light guide 41 is provided. If required, the light guide can be curved along its length, as shown in Figure 5, to direct the output beam to suit a particular application, this being a known practice with existing light guides. The light guide may be machined from cast acrylic plastic and bent, or could be made from glass or other optically transparent materials.

An alternative light guide is illustrated in Figure 8 in which the bend in the light guide 41 is provided at a waisted section 46 in its length which reduces to a minimum diameter

before widening again to a larger diameter towards its output end. By forming the bend at the minimum diameter, the light transmission losses of the light guide caused by the bend are reduced, but the effective cross-sectional area of the output beam is maintained at the required level.

Fused fibre-bundle light guides have the advantage of individual fibres being of a relatively small diameter so that they can be bent over a tighter radius without the greater losses associated with larger diameter fibres when bent over the same radius. However, conventional fused-fibre bundles have the disadvantage of a packing fraction loss, that is, the outer cladding of the fibre uses up a significant proportion of the cross-section of the light guide into which light from the semiconductor array is directed, thus reducing the amount of transmitted radiation available from the semiconductor source. Preferably, therefore, in one embodiment of the invention, illustrated in Figure 7, the guide comprises a few shaped fibres 61 placed adjacent to each other and fused together. A guide of this design is manufactured by MicroQuartz Sciences Inc. of Phoenix, Arizona, USA. In this way, the diameter of each fibre is smaller than a single homogeneous guide rod so that they allow greater light transmission on bending around the same bend radius, but also the packing fraction is also greatly reduced over conventional

fibre guides, resulting in a greater than 90% core availability at the input end of the guide.

In another embodiment of the invention, a graded-index optical light guide is used. A graded-index light guide has no sudden interface between the cladding and the core. Instead, the refractive index varies either radially or axially. In one embodiment, the gradient of the refractive index of the light guide varies both radially and axially so that the light energy is favourably manipulated. A guide that uses a stepped index could also be used with the same axial and radial variation in refractive index. In this way, the numeric aperture can be varied at either end of the guide to achieve the desired transmission.

In other embodiments of the invention, instead of providing a single tapered light guide, each LED or groups of LEDs could be provided with its own light guide fibre incorporating an adiabatic optical taper, and the output ends of these fibres could be collected together to form a single output beam. The input end of the fibre would be moulded optically to the adjacent LED or group of LEDs for efficient transmission of radiation. In this way, the diodes can be spaced more widely to dissipate unwanted heat. In yet another embodiment of the invention, each LED could be adjusted so that its outer envelope is extended into a fibre light guide which

incorporates an adiabatic optical taper. In yet another embodiment, the section of the fibres may be modified so that shaped faces of the fibres fit together to reduce the interstitial space. One embodiment of this design could be as shown in Figure 7.

The light guide or light guides used according to the invention may be formed with an outer metallic coating to improve its performance.

It will be appreciated that the irradiance of the device according to the invention can be varied by varying the input power, number of LEDs, or by varying the adiabatic taper of the light guide.

Cooling of the LED cluster can be aided according to another feature of the invention by arranging that the electrical connections of each LED are thermally connected to one or more heat pipes. Conventional LED irradiation devices usually include a heat sink to conduct away the heat from the LED chips. Heat sinks are generally slow and inefficient in conducting heat away from a heat source compared with heat pipes. Heat pipes conduct heat away rapidly by using the latent heat of a substance, such as water, which is vaporised by the heat from the source. The vapour moves at high speed to the cooler end of the heat pipe and condenses. Heat pipes

are unique in their ability to conduct heat rapidly in this way.

Figure 5 shows a device according to the invention which incorporates a heat pipe 45 as a single lumen in the main body 46 of the device. The hotter of the LED leads is preferably placed nearer the heat pipe 45 or outer case 47 of the LED cluster so that the heat path of the hotter lead is shorter.

A thermal connector 48 may be provided between the LEDs 43 and the end of the heat pipe 45. If required, additional forced cooling means may be used for example, a fan 49 or Peltier device 50 in juxtaposition to the pipe. In addition, a heat sink 51 may be provided.

Because of the greater cooling ability of heat pipes, they allow the LEDs to be driven in such a manner as to produce more radiation, and thus allows a more powerful device to be manufactured.

For portable use, the LEDs are operated from batteries 52, which are located in a hand grip 53 attached to the body 46, in Figure 5. However, the heat pipe design can be modified as shown in Figure 9 to accommodate batteries. The heat pipe consists of two concentric heat conducting tubes 55, 56 with a folded interstitial heat conduction element 57 between these tubes similar in appearance to a length of corrugated

sheet rolled into a tube. This lies within the concentric tubes. The wicks 58 of the heat pipe can then be placed in alternative grooves in the corrugated sheet, while the empty grooves 59 allow for the rapid movement of the vapour formed at the warmer end of the heat pipe.

By designing the heat pipe in this way batteries, capacitors, supercapacitors or other energy source 60 can be located within the inner wall 55 of the heat pipe.

In some embodiments, for example, where there are a large number of LEDs, a heat sink 51 may be necessary in addition to the heat pipe 45. The intermittent use of an LED irradiation device for dental curing, means that with careful design, a heat sink may be omitted. If cooling to below the ambient temperature is required, such as may be the case in extreme environments, a Peltier device 50 may be added to the heat pipe, although a Peltier device will result in a greater consumption of power and a requirement for greater heat dissipation.

The wavelengths of the LED used will depend upon the applications of the device. A LED emitting blue light with a peak wavelength of about 470nm is used to harden dental polymers, but a LED emitting red light may be useful for photodynamic therapy, for example, cancer therapy.

The wavelength of light emitted by the LEDs may be modified in a light guide by doping the material from which it is composed with fluorescent material. This can serve to lengthen the wavelength of the emitted light so as to suit the particular application.

The choice of LED is also important in terms of its construction, diameter, irradiance and light angular spread pattern. From a range of known LEDs the best available choice has been determined as that with a 3mm diameter rather than a 5mm diameter and an angular spread of 30 degrees rather than 15 or 45 degrees. Nichia is the manufacturer of these LEDs.

It will be appreciated that the term "light-emitting diode-LED" as used herein also includes laser diodes.

LEDs in the devices according to the invention may be operated in a pulsed mode or modulated mode to vary the output radiation intensity to suit the application, and multiple clusters of LEDs, such as in the embodiment of Figure 6, may each be generated in a different mode.

The power supply for the LEDs of the device according to the invention could be mains power, battery power, capacitor,

In one embodiment, a capacitor or supercapacitor could be used to power the array having advantages over conventional rechargeable sources such as batteries. Capacitors can be virtually instantaneously recharged between one or more curing cycles of operation when the unit is connected to a power source.

The power supply for the device may be re-chargeable, and may be designed to make automatic electrical contact with the charging means of a base unit when engaged with the latter in the manner of a cordless telephone handset.

CLAIMS

1. An optical irradiation device comprising an array of light-emitting diodes (LEDs) clustered so that radiation they emit is directed into a beam characterised in that each LED is formed with multiple facets such that the facets of adjacent LEDs adjoin one another in close proximity throughout their length.
2. A device as claimed in claim 1 in which the facets of adjacent LEDs extend substantially parallel to one another.
3. A device as claimed in claim 1 in which the facets of adjacent LEDs abut one another.
4. A device as claimed in claim 1 in which LEDs are arranged in a ring with side facets of adjacent LEDs adjoining one another.
5. A device as claimed in claim 4 in which LEDs are arranged in concentric rings with side facets of adjacent LEDs in each ring adjoining one another.
6. A device as claimed in claim 5 in which the LEDs of adjacent rings have radially directed facets adjoining one another.
7. A device as claimed in claim 4 in which a single LED is located within said ring or innermost concentric ring.

8. A device as claimed in claim 7 in which said single LED has radially directed facets that adjoining facets of the LEDs in said ring or innermost concentric ring.
9. A device as claimed in claim 1 in which the LEDs are regular polygons in cross-section.
10. A device as claimed in claim 9 in which the LEDs are hexagonal in cross-section.
11. A device as claimed in claim 1 in which the facets of the LEDs are polished.
12. A device as claimed in claim 1 in which the facets of the LEDs are provided with a reflective coating.
13. A diode adapted for use in an optical irradiation device as claimed in claim 1.
14. A device as claimed in claim 1, including a light guide for collecting light from the cluster of light emitting diodes.
15. A device as claimed in claim 1, wherein a light guide is provided for each light emitting diode in the cluster.

16. A device as claimed in claim 1 including a light guide for collecting light from the cluster of LEDs, the light guide having an index that varies from one part to another so as to manipulate the light.
17. A device as claimed in claim 1 including a light guide that consists of a few fibres formed individually before being bundled together.
18. A device as claimed in claim 1 including a light guide consisting of shaped fibres packed together so that the packing fraction is reduced.
19. An irradiation device employing LEDs and a tapered light guide to collect radiation emitted by the LEDs and deliver this to an output beam, characterised in that two or more tapered light guides are arranged in series so that successive guides receive radiation from preceding guides, and an LED or group of LEDs is provided at the input end of each guide.
20. A device as claimed in claim 20 in which each successive guide is provided with a ring of LEDs around the output end of the preceding guide.
21. A device as claimed in claim 1 in which the heat is removed from the LEDs by a heat pipe.

22. A device as claimed in claim 21 in which a plurality of heat pipes is used to transfer heat from the LEDs.
23. A device as claimed in claim 21 in which an annular heat pipe is used so that it can contain energy storage means.
24. A device as claimed in claim 1, including a Peltier device to cool the LEDs.
25. A device as claimed in claim 1 having a pistol grip to contain energy storage means.
26. A device as claimed in claim 1, including a capacitor or supercapacitor to power the device.
27. An optical irradiation device comprising a plurality of LEDs and a heat pipe to cool the LEDs.
28. A hand-held device for curing dental materials including an optical irradiation device as claimed in claim 1.
29. A heat pipe comprising inner and outer walls that extend longitudinally from one end of the heat pipe to the other and define an annular space therebetween containing a material that serves to absorb heat by a phase change, the annular space being divided by

30. A tapered light guide for an optical irradiation device, which light guide is tapered from its input end to its output end and has an intermediate region of minimum diameter in which a bend is formed.

(FIGURE 4)

ABSTRACT**OPTICAL IRRADIATION DEVICE**

An optical irradiation device incorporating a cluster of LEDs (11, 43) arranged so that shaped facets of adjacent LEDs come together to increase the packing density of LEDs in the cluster. A light guide (41) collects light emitted by the LEDs. Two or more light guides (41) and LED clusters (43) may be arranged in series to produce a single light beam. A heat pipe (45) is provided to conduct heat away from the LEDs (43). The heat pipe (56) may be annular and contain an inner storage space for batteries (60) or the like.



FIG. 4





FIG. 5




FIG. 6




FIG. 7



Attorney's Docket No. P-3002.1**COMBINED DECLARATION AND POWER OF ATTORNEY**(ORIGINAL, DESIGN, NATIONAL STAGE OF PCT, SUPPLEMENTAL,
DIVISIONAL, CONTINUATION OR CIP)

As a below named inventor, I hereby declare that:

TYPE OF DECLARATIONThis declaration is of the following type: *(check one applicable item below)*

- ☒ original
☐ design
☐ supplemental

NOTE: If the declaration is for an international Application being filed as a divisional, continuation or continuation-in-part application do not check next item; check appropriate one of last three items.

☐ national stage of PCT

NOTE: If one of the follow 3 items apply, then complete and also attach ADDED PAGES FOR DIVISIONAL, CONTINUATION OR CIP.

- ☐ divisional
☐ continuation
☐ continuation-in-part (CIP)

INVENTORSHIP IDENTIFICATION

WARNING: If the inventors are each not the inventors of all the claims an explanation of the facts, including the ownership of all the claims at the time the last claimed invention was made, should be submitted.

My residence, post office address and citizenship are as stated below next to my name, I believe I am the original, first and sole inventor *(if only one name is listed below)* or an original, first and joint inventor *(if plural names are listed below)* of the subject matter which is claimed and for which a patent is sought on the invention entitled:

TITLE OF INVENTION

OPTICAL IRRADIATION DEVICE

SPECIFICATION IDENTIFICATION

the specification of which: (complete (a), (b) or (c))

- (a) ☐ is attached hereto.
 (b) ☒ was filed on 3/24/2000 as Serial No. 09/509,433 or Express Mail No., _____ as
 Serial No. not yet known _____ and was amended on _____ (if applicable).

NOTE: Amendments filed after the original papers are deposited with the PTO which contain new matter are not accorded a filing date by being referred to in the declaration. Accordingly, the amendments involved are those filed with the application papers or, in the case of a supplemental declaration, are those amendments claiming matter not encompassed in the original statement of invention or claims. See 37 CFR 1.67.

(c) X was described and claimed in PCT International Application No. PCT/GB98/02905 filed on 9/25/98 and as amended under PCT Article 19 on _____ (if any).

ACKNOWLEDGEMENT OF REVIEW OF PAPERS AND DUTY OF CANDOR

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information

X which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations. § 1.56.

(also check the following items, if desired)

X and which is material to the examination of this application, namely, information where there is a substantial likelihood that a reasonable examiner would consider it important in deciding whether to allow the application to issue as a patent, and
_____ In compliance with this duty there is attached an information disclosure statement 37 CFR 1.97.

PRIORITY CLAIM

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed.

(complete (d) or (e))

(d) _____ no such applications have been filed.

(e) X such applications have been filed as follows

NOTE: Where item (c) is entered above and the International Application which designated the U.S. claimed priority check item (e), enter the details below and make the priority claim.

**A. PRIOR FOREIGN/PCT APPLICATION(S), IF ANY FILED WITHIN 12 MONTHS
(6 MONTHS FOR DESIGN) PRIOR TO THIS U.S. APPLICATION AND ANY PRIORITY
CLAIMS UNDER 35 U.S.C. § 119**

COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIM UNDER 35 USC 119
GB	9720443.2	25. 09. 97	Yes
GB	9806046.0	20.03.98	Yes

(Declaration and Power of Attorney page 2 of 5)

CHECK PROPER BOX(ES) FOR ANY OF THE FOLLOWING ADDED
PAGE(S) WHICH FORM A PART OF THIS DECLARATION

☐ Signature for fifth and subsequent joint inventors. Number of pages added ☐

☐ Signature by administrator(trix), executor(trix) or legal representative for deceased or incapacitated inventor. Number of pages added ☐

☐ Signature for inventor who refuses to sign or cannot be reached by person authorized under 37 CFR 1.47.
Number of pages added ☐

* * *

☐ Added pages to combined declaration and power of attorney for divisional, continuation, or continuation-in-part (CIP) application.

☐ Number of pages added ☐

* * *

☐ Authorization of attorney(s) to accept and follow instructions from representative.

* * *

If no further pages form a part of this Declaration then end this Declaration with this page and check the following item

☒ This declaration ends with this page.

DECLARATION

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

SIGNATURE(S)

Full name of sole or first inventor

Robin Walter Mills
(Given Name) (Middle Initial or Name) Family (or Last) Name

Inventor's signature X RW Mills

Date X 19 April 2000 Country of Citizenship United Kingdom GBX

Residence 9 Kempsfiel

Post Office Address Devizes

Wiltshire SN10 5AX United Kingdom

Full name of second joint inventor, if any

Klaus Dieter Jandt
(Given Name) (Middle Initial or Name) Family (or Last) Name

Inventor's signature X K. Jandt

Date X 4 May 2000 Country of Citizenship United Kingdom GBX

Residence 21 Cranmoor Green

Post Office Address Bristol BS35 4QF

United Kingdom GBX

Full name of third joint inventor, if any

(Given Name) (Middle Initial or Name) Family (or Last) Name

Inventor's signature _____

Date _____ Country of Citizenship _____

Residence _____

Post Office Address _____

ALL FOREIGN APPLICATION(S), IF ANY FILED MORE THAN 12 MONTHS
(6 MONTHS FOR DESIGN) PRIOR TO THIS U.S. APPLICATION

POWER OF ATTORNEY

As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (List name and registration number)

E.J. Biskup	<u>18,987</u>	E.T. Jones	<u>40,037</u>
R.C. Collins	<u>27,430</u>	J.F. Learman	<u>17,069</u>
P.J. Ethington	<u>17,299</u>	J.K. McCulloch	<u>17,451</u>
J.C. Evans	<u>20,124</u>	J.P. Moran	<u>20,941</u>
R.L. Farris	<u>25,122</u>	S.L. Permut	<u>28,388</u>
W.H. Francis	<u>25,335</u>	M.J. Schmidt	<u>43,904</u>
F.J. Fodale	<u>20,824</u>	W.J. Schramm	<u>24,795</u>
W.H. Griffith	<u>16,706</u>	R.L. Stearns	<u>36,937</u>
A.M. Grove	<u>39,697</u>	J.D. Stevens	<u>35,691</u>
R.W. Hoffman	<u>337114</u>	W.J. Waugaman	<u>20,304</u>
		C.R. White	<u>20,494</u>

SEND CORRESPONDENCE TO John C. Evans DIRECT TELEPHONE CALLS TO:
(Name and telephone number)

John C. Evans
Reising, Ethington, Barnes,
Kisselle, Learman & McCulloch, P.C.
P.O. Box 4390
Troy, MI 48099-4390

John C. Evans
(248) 689-3500